

MIZU Mounting Instructions System 1

Ride height lowering kit

You have chosen a MIZU product, which is made under the strict MIZU specifications and offers the highest quality and safety standards. Please follow these instructions for the MIZU ride height lowering kit.

General Information:

In general we suggest visiting a motorcycle repair shop or dealership to install our products. Know how and experience of a motorcycle shop cannot be compensated by this manual. Please ensure a stable stand of the bike. This product can only be used for the model indicated and mentioned on the application list. Do not use this product on any other bike model, year or type or another manufacturer. Always utilize the torsion torque specified by the manufacturer.

Before Installing:

Please read the instruction manual carefully before installation. Make sure, that you have all tools required and that they are in good condition. Protect the bike in the area of installation from scratches, dents etc by covering the bike with a blanket or something similar. For easy installation, the bikes rear wheel should have about 2 inches (4-5 cm) of ground clearance.

During installation:

Check all parts before, while and after every installation step. Clean and degrease all parts before installation. Please be careful while installing, so there is no damage or scratches to the motorcycle. Please work relaxed and concentrated to avoid mistakes or the risk damaging any parts.

After installation:

Check and make sure that the lowering kit has no contact to any other parts on the bike. The kit cannot touch anything else. If the movement of the springs are affected, then change the position of the affected parts (i.e. luggage carrier etc.) in a way, that the springs movement is no longer affected. Please check all screws and nuts after installation.

Attention!

In general it's essential to adjust the base weight to the conditions. Please take the riders weight and spring rate into consideration. In general most manufacturers base the springs they use to a weight of 85 kg or about 187 lbs.

Before every ride, check the function and movement and function of the shocks

Step 1: Mounting of the ride height lowering kit (contingent on model)

Loosen the nuts of the original shock link with the proper tools. Remove the original shock link and replace them with the MIZU lowering kit. The lowering kit is typically 3-10 millimetres shorter than the stock part. The part marking (MIZU-302...) should be visible on the outside. Please use new nuts and bolts, depending on the model and recommendation by the manufacturer. Please also adhere to the required torsion ratios recommended by the manufacturer. After the installation check the use and function of the brake line and the shock.

Important note:

Whit a lowering kit the chain tension is a little lower and needs to be adjusted. Please always check the chains tension and adjust the chain as specified by the manufacturer. Please always make sure the bike has a safe stand when parked, depending on the model the side and center stand need to be adjusted. The degree of the rising kit is measured vertical to the rear axle and fluctuates depending on the adjustment and wearing of the rear suspension. Please contact us for any question or concerns you might have. Call (+49) 7731-90670

Have Fun Riding !

YOUR MIZU TEAM

